

§ 1917.24

(2) Persons entering a space containing a hazardous atmosphere shall be instructed in the nature of the hazard, precautions to be taken, and the use of protective and emergency equipment. Standby observers, similarly equipped and instructed, shall continuously monitor the activity of employees within such space;

(3) Except for emergency or rescue operations, employees shall not enter into any atmosphere which has been identified as flammable or oxygen deficient (less than 19.5% oxygen). Persons who may be required to enter flammable or oxygen deficient atmospheres in emergency operations shall be instructed in the dangers attendant to those atmospheres and instructed in the use of self-contained breathing apparatus, which shall be utilized.

(4) To prevent inadvertent employee entry into spaces that have been identified as having hazardous, flammable or oxygen deficient atmospheres, appropriate warning signs or equivalent means shall be posted at all means of access to those spaces.

(e) When the packaging of asbestos cargo leaks, spillage shall be cleaned up by designated employees protected from the harmful effects of asbestos as required by § 1910.1001 of this chapter.

[48 FR 30909, July 5, 1983, as amended at 49 FR 28551, July 13, 1984; 61 FR 5509, Feb. 13, 1996; 62 FR 40197, July 25, 1997; 65 FR 40938, June 30, 2000]

§ 1917.24 Carbon monoxide.

(a) *Exposure limits.* The carbon monoxide content of the atmosphere in a room, building, vehicle, railcar, or any enclosed space shall be maintained at not more than 50 parts per million (ppm) (0.005%) as an eight hour average area level and employees shall be removed from the enclosed space if the carbon monoxide concentration exceeds a ceiling of 100 ppm (0.01%).

(b) *Testing.* Tests to determine carbon monoxide concentration shall be made when necessary to ensure that employee exposure does not exceed the limits specified in paragraph (a) of this section.

(c) *Instrumentation.* Tests for carbon monoxide concentration shall be made by designated persons using gas detector tube units certified by NIOSH

29 CFR Ch. XVII (7–1–14 Edition)

under 30 CFR part 11 or other measuring instruments whose accuracy is as great or greater.

(d) *Records.* A record of the date, time, location and results of carbon monoxide tests shall be available for at least thirty (30) days.

[48 FR 30909, July 5, 1983, as amended at 49 FR 28551, July 13, 1984; 61 FR 5509, Feb. 13, 1996; 62 FR 40197, July 25, 1997]

§ 1917.25 Fumigants, pesticides, insecticides and hazardous preservatives (see also § 1917.2 Hazardous cargo, material, substance or atmosphere).

(a) At any time that the concentration in any space reaches the level specified as hazardous by the fumigant manufacturer or by Table Z-1 of 29 CFR 1910.1000, whichever is lower, all employees shall be removed from the space and shall not be permitted to re-enter until such time as tests demonstrate that the atmosphere is safe.

(b) Tests to determine the atmospheric concentration of chemicals used to treat cargo shall be:

(1) Appropriate for the hazard involved;

(2) Conducted by designated persons; and

(3) Performed at the intervals necessary to ensure that employee exposure does not exceed the permissible exposure limit for the chemical involved.

(c) Results of any tests shall be available for at least 30 days. Such records may be entered on any retrievable medium, and shall be available for inspection.

(d) Chemicals shall only be applied to cargoes by designated persons.

(e) Only designated persons shall enter hazardous atmospheres, in which case the following provisions apply.

(1) Persons entering a space containing a hazardous atmosphere shall be protected by respiratory and emergency protective equipment meeting the requirements of subpart E of this part; and

(2) Persons entering a space containing a hazardous atmosphere shall be instructed in the nature of the hazard, precautions to be taken, and the use of protective and emergency equipment. Standby observers, similarly